Makoswater ...nature is the key

TANKS AND SUCTION LANCE





SUCTION LANCE

L - SUCTION LANCES WITH FOOT FILTER



AC LA SERIES

- · Available with level probe
- FPM seals (EPDM upon request)
- Made of PVC/PP with PVC Crystal suction tube

All the suction lances are equipped with foot valves PVC/SS316L propeller, 2, 3, 6 blades (flat or with holes), diameter 90, 150, 220 mm (other lengths

diameters upon request)

MODELS	DIMENSIONS	TUBES	FOR TANKS
4614.05	450x22mm	4x6	50 lt
AC LA 05	450x34mm	8x12	50 lt
AC A 1	650x22mm	4x6	100 lt
AC LA 1	650x34mm	8x12	100 lt
46143	900x22mm	4x6	250 lt
AC LA 2	900x34mm	8x12	250 lt
AC LA 3	1050x22mm	4x6	300 lt
AC LA 3	1050x34mm	8x12	300 lt
ACLA F /10	1250x22mm	4x6	500/1000 lt
ACLA 5/10	1250x34mm	8x12	500/1000 lt

- POLYETHYLENE TANKS



AC SE SERIES

 Suggested for the assembling of dosing groups with mixers, electromechanic and electromagnetic dosing pumps. They grant a high mechanical resistance obtained through centrifugal. Force compatible with all chemicals used in the dosing groups

MODELS	CAPACITY	HEIGHTS	DIAMETERS
AC SE 05	50 lt	455mm	40cm
AC SE 1	100 lt	640mm	45cm
AC SE 2	250 lt	870mm	60cm
AC SE 3	300 lt	950mm	67cm
AC SE 5	500 lt	1185mm	76cm
AC SE 10	1000 lt	122mm	108,5cm



AC VA SERIES

Polyethylene uncovered tanks, designed to contain our tank

MODELS	CAPACITY	HEIGHTS	DIAMETERS
AC VA 1	150 lt	755mm	510mm
AC VA 2	300 lt	875mm	670mm
AC VA 3	400 lt	990mm	720mm
AC VA 5	800 lt	1200mm	900mm
AC VA 10	1500 lt	1340mm	1220mm



AC SU SERIES

 Re-inforced PVC tanks to be used for installing mixers and motor driven or solenoid dosing pumps

MODELS	FOR TANKS	HEIGHTS
AC SU 1	AC SE 1	20mm
AC SU 2	AC SE 2	20mm
AC SU 3	AC SE 3	20mm
AC SU 5	AC SE 5	20mm
AC SU 10	AC SE 10	20mm

